Panda 10000x-400V PVK-UK

FischerPanda

Article:

General Technical Data

Vehicle Generator designed for external installation with integrated water-cooled exhaust and radiator

Generator Type	xSeries - Compact Power
Generator Family	10000x
Generator Version	PVK-UK
Area of Application	Vehicle
Capsule Type	MPL 4DS
Generator Manufacturer	Fischer Panda GmbH
Windings Isolation Class	H
Control System	xControl / fpControl
Voltage Tolerance	3V
Cos Phi	0.85
Sound Levels dB(A) [7m/3m/1m]	52 / 62 / 67
Weight (kg)	340
Capsule Dimensions (excl. fittings)	1516 x 522 x 620

Electrical Alternator

Engine Speed [rpm]	3000
Voltage	400
Frequency [Hz]	50
Number Phases	3
Nominal Performance [kW]	8,0
Nominal Performance [kVA]	9,4

Engine

Engine Manufacturer	Kubota
Engine Type	KU Z602
No. Cylinders	2 cylinder Diesel
Displacement [cm3]	599
Starter System	12 V
Emission Regulations	US 40CFR 1039
	EU 2016/1628
	China 20891-2014

Service / Installations Kits/ Shock mountings

Service Kit	Request
Service Kit “Plus”	Request

Generator Capsule / Sound Shield

LEARN MORE

Disclaimer: The information contained here is to the best of our knowledge accurate at the date of publication. Please note that the data in this publication reflects the technical state at time of print. Due to our policy of continual product development, we reserve the right to alter technical specifications without notice. The technical parameters / output performance may vary for different generator types and exhaust emission norms for different countries. All performance data applies to generator operation at 100m above sea level at 20°C. Performance reductions can occur when operating at greater heights.