

Panda 18x PVK-UK



Article: 0005333

General Technical Data

Vehicle Generator designed for external installation with integrated water-cooled exhaust and radiator

Generator Type	Compact Power
Generator Family	18x
Generator Version	PVK-UK
Area of Application	Vehicle
Capsule Type	MPL 4DS
Generator Manufacturer	Fischer Panda GmbH
Windings Isolation Class	H
Control System	xControl / fpControl
Voltage Tolerance	3V
Cos Phi	0.85
Sound Levels dB(A) [7m/3m/1m]	55 / 65 / 69
Weight (kg)	544
Capsule Dimensions (excl. fittings)	1736 x 560 x 680




Electrical Alternator

Engine Speed [rpm]	3000
Voltage	230
Frequency [Hz]	50
Number Phases	1
Nominal Performance [kW]	15,3
Nominal Performance [kVA]	18,0

Engine

Engine Manufacturer	Kubota
Engine Type	KU D1105
No. Cylinders	3
Displacement [cm ³]	1123
Starter System	12 V
Emission Regulations	

Generator Capsule / Sound Shield



Service / Installations Kits/ Shock mountings

Service Kit	0000694
Service Kit "Plus"	0006368
Shock mounting, captive	0002754

[LEARN MORE](#)



Disclaimer: The information contained here is to the best of our knowledge accurate at the date of publication. Please note that the data in this publication reflects the technical state at time of print. Due to our policy of continual product development, we reserve the right to alter technical specifications without notice. The technical parameters / output performance may vary for different generator types and exhaust emission norms for different countries. All performance data applies to generator operation at 100m above sea level at 20°C. Performance reductions can occur when operating at greater heights.